



PROMOCLEAN[™] TP 1117

REMOVAL OF POLISHING PASTE & OIL AQUEOUS IMMERSION PROCESS COMPATIBLE WITH MOST ALLOYS & 3-7 DAYS CORROSION PROTECTION

BENEFITS

PROMOCLEAN TP 1117 is especially designed for removal of polishing pastes, hydrocarbon & water-soluble oils. It is dedicated for aqueous immersion process with ultrasonic agitation.

Thanks to its medium pH, it doesn't damage most ferrous and sensitive non-ferrous alloys, like lnox, Aluminium, Titanium, Copper, Brass. It can also be used on precious metals such as gold and silver.

Additional, PROMOCLEAN TP 1117 provides a temporary protection against corrosion thanks to its passivation properties. This makes the product particularly suitable for inter-operation before the next operational step, leaving the parts protected for 3-7 days (depending on local humidity level and temperature).

It's a concentrated product which is used diluted with DI water or tap water.

PERFORMANCE	 Cleans efficient most metals, including very sensitive ones. Excellent dispersion of polishing compounds Does not leave spots or residues Good temporary protection against corrosion
COST	High cleaning power even at low concentrationVery long bath-life
HSE	Non-toxic & no CMR substancesNon-flammable

SPECIFICATIONS

SPECIFICATIONS	VALUES	METHODS
Aspect	Light brown	Visual
Density at 20°C (g/ml)	1,05 ± 0,01	BRY-MO-028
pH of pure product	10,8 ± 0,5	BRY-MO-011

CHARACTERISTICS

CHARACTERISTICS	VALUES	
Solubility in water	totally soluble	
Surface tension at 1%	28 Dynes /cm2	

PROMOCLEAN TP 1117 PDS2023-05 ENV

PROCESS RECOMMENDATION

The best process will depend on factors such as operating conditions, equipment, desired cleaning time and the nature of contaminants. Our team is ready to advise you.

PROCESS EXAMPLE

Oil removal with temporary corrosion protection

PROMOCLEAN TP 1117

DI WATER

PROMOCLEAN TP 1117

HOT AIR

or

VACUUM

or

VACUUM

or

DRYING SOLVENT

Temp: 40-70°C / 104-158°F

US: yes

Time: 3-10 min

CLEANING

PROMOCLEAN TP 1117

HOT AIR

or

VACUUM

OR

DRYING SOLVENT

Time: 1-3 min

Time: 5-20 min

DRYING

DRYING

- For cleaning hard to remove polishing pastes, other products from the PROMOCLEAN range could be used in combination with PROMOCLEAN TP 1117 in order to improve process efficiency.
- Increasing the bath-life of your process can be achieved by adding an oil separator within the cleaning equipment and to add
 periodically concentrated product.
- Compatibility report with different materials is available on request.
- Concentration can be monitored with a dedicated PCA KIT or with our PCA DIGITAL online analysing equipment.
- It's key to determine the maximum time materials can be exposed to the cleaning chemical. Although our cleaning products will not damage materials they are designed for under normal conditions, prolonged exposure may.

PACKAGING, STORAGE & SHELF LIFE

- Keep products in closed original packaging and store at room temperature.
- Shelf life is minimum 18 months from production date when kept in recommended conditions.

AVAILABLE PACKAGING



HEALTH, SAFETY & ENVIRONMENT

PROMOCLEAN TP 1117 is **NOT** a **GREENWAY** product. Although fully in line with safety & environmental regulations, this product doesn't match our strict criteria to be labelled as a Greenway product. More info on our Greenway concept via this <u>link</u>.



LOOKING FOR A MORE SUSTAINABLE SOLUTION?

GREENWAY ALTERNATIVE

Promoclean TP 1114

Contains no Reach Substances (on Candidate list, Annex XIV & XVII) / Contains no persistent organic pollutant (EC 850/2004) / Contains no Import/Export Hazardous substances (EU 649/ 2012)

It is biodegradable according to regulation 648/2004 but must be neutralized and filtered before disposal in sewer system in accordance with local regulations. Neutralization and titration methods are available upon request.

Please refer always to the Safety Data Sheet (SDS or MSDS) prior to use. Our SDS can be downloaded at www.quickfds.com. We will request to provide your email address, so we can automatically send you a new version of the SDS when a future update would occur.



PROMOCLEAN TP 1117 PDS2023-05 ENV

TECHNICAL SUPPORT & FREE-OF-CHARGE TESTING

Inventec has a worldwide dedicated Technical Support team to help you along the different stages of our cooperation.

Depending on your request, we provide online or onsite support

- to select the right product based on your specific needs
- to assist you in your product qualification process
- to guide you with the initial set up of you process at all your worldwide manufacturing facilities
- to provide fast response on technical issues which could occur at any time during mass production

Customers are also welcome in our CLEANING CENTERS to see the process in action and to get convinced by our solutions. We cover water- and solvent based processes.

Inventec is unique in the world by developing not only cleaning materials but also soldering and coating solutions. These materials are very closely linked with each other from a process point of view. Talking to our Technical Team, who understands very well these 3 different product groups, will help you greatly to overcome technical challenges within your overall process.

Contact our technical support via contact@inventec.dehon.com or your local sales representative.

ABOUT INVENTEC

Inventec is a global provider of SOLDERING, CLEANING & COATING materials for Electronic, Semiconductor and Industrial applications. For over 60 years we have shown leadership in innovation by putting HEALTH IMPACT, SUSTAINABILITY and RELIABILITY at the core of our product development.

With ISO 9001 & 14001 production sites in France, Switzerland, USA, Mexico, Malaysia and China we can guarantee a smooth and cost-effective supply chain.

We supply to many industries but the excellent performance of our products in applications which demand high reliability, leads us to focus especially on the AUTOMOTIVE, AEROSPACE, SEMICONDUCTOR, ENERGY and MEDICAL industry.

www.inventec.dehon.com



SOLDERING
CLEANING
COATING
COOLING

In accordance with the Annex II of Directive 2011/65/UE (RoHS), including its amendments, we certify that this product does not contains quantities above 0.1% of Hg, Pb, Cr VI, PBB, PBDE, DEHP, BBP, DBP, DIBP and above 0.01% of Cd.

This data is based on information that the manufacturer believes to be reliable and offered in good faith. In no event will INVENTEC PERFORMANCE CHEMICALS be responsible for special, incidental and consequential damages. The user is responsible to the Administrative Authorities (regulations for the protection of the Environment) for the conformity of his installation.

Inventec Performance Chemicals – 26 rue de Coulons. 94360 Bry-sur-Marne, France Limited company with capital of 600 000€ - 964 500 706 RCS Créteil

