



CLEANING

PROMOCLEAN™ DISPER 22

REMOVAL OF GREASE, HEAVY OIL, BURN-IN RESIDUES & OXIDES
 AQUEOUS SPRAY PROCESSES
 COMPATIBLE WITH FERROUS ALLOYS

BENEFITS

PROMOCLEAN DISPER 22 is especially designed for removal of greases, heavy (high viscosity) oils, burn-in organic & mineral residues and oxides. Thanks to its excellent antifoam properties it is dedicated for aqueous spray-in-air, immersed jets and tube flushing processes.

Despite having a high pH to allow efficient cleaning, it doesn't damage ferrous alloys. It is however not suitable for sensitive metals like aluminium and other light alloys. For these alloys we recommend PROMOCLEAN DISPER 22 ALU.

It's a concentrated product which is used diluted with DI water.

PERFORMANCE	<ul style="list-style-type: none"> ▪ Cleans efficiently ferrous metals ▪ High pH permit to remove broad spectrum of mineral & organic pollutants in large quantities
COST	<ul style="list-style-type: none"> ▪ High cleaning power even at low concentration ▪ Long bath-life ▪ Versatile application: can be used in production & maintenance
HSE	<ul style="list-style-type: none"> ▪ Non-toxic & no CMR substances ▪ Non-flammable & will not cause an exothermic reaction in the cleaning tank

SPECIFICATIONS

SPECIFICATIONS	VALUES	METHODS
Aspect	Colorless to yellow liquid	Visual
Density at 20°C (g/ml)	1,49 ± 0,01	BRY-MO-028
pH at 1%	12,8 ± 0,5	BRY-MO-011

CHARACTERISTICS

CHARACTERISTICS	VALUES
Solubility in water	totally soluble
Refractive index at 20°C	1,43

PROCESS RECOMMENDATION

The best process will depend on factors such as operating conditions, equipment, desired cleaning time and the nature of contaminants. Our team is ready to advise you.

PROCESS EXAMPLE

Heavy oil & grease removal

<p>PROMOCLEAN DISPER 22</p> <p>Conc: 1-5% in DI water Temp: 40-70°C / 104-158°F US: No Time: 5-10 min</p>	<p>DI or TAP WATER</p> <p>Temp: 20-30°C / 68-86°F US: No Time: 2-5 min</p>	<p>HOT AIR or VACUUM or DRYING SOLVENT</p> <p>Time: 5-20 min</p>
CLEANING	RINSING	DRYING

Removal of burn-in residues

<p>PROMOCLEAN DISPER 22</p> <p>Conc: 5-20% in DI water Temp: 40-70°C / 104-158°F US: no Time: 5-10 min</p>	<p>DI or TAP WATER</p> <p>Temp: 20-30°C / 68-86°F US: no Time: 2-5 min</p>	<p>HOT AIR or VACUUM</p> <p>Time: 5-20 min</p>
CLEANING	RINSING	DRYING

- A dedicated PCA Kit to monitor the bath status and compatibility report with different materials are available on request.
- It's key to determine the maximum time materials can be exposed to the cleaning chemical. Although our cleaning products will not damage materials they are designed for under normal conditions, prolonged exposure may.

PACKAGING, STORAGE & SHELF LIFE

- Keep products in closed original packaging and store at room temperature.
- Shelf life is minimum 18 months from production date when kept in recommended conditions.

AVAILABLE PACKAGING



20 Kg CANISTER




210 Kg DRUM

HEALTH, SAFETY & ENVIRONMENT

PROMOCLEAN DISPER 22 is **NOT** a **GREENWAY** product. Although fully in line with safety & environmental regulations, this product doesn't match our strict criteria to be labelled as a Greenway product.

More info on our Greenway concept via this [link](#)



LOOKING FOR A MORE SUSTAINABLE SOLUTION?

GREENWAY ALTERNATIVE

- Promoclean Disper 2

Contains no Reach Substances (on Candidate list, Annex XIV & XVII) / Contains no persistent organic pollutant (EC 850/2004) / Contains no Import/Export Hazardous substances (EU 649/ 2012)

It is biodegradable according to regulation 648/2004 but must be neutralized and filtered before disposal in sewer system in accordance with local regulations. Neutralization and titration methods are available upon request.

Please refer always to the Safety Data Sheet (SDS or MSDS) prior to use. Our SDS can be downloaded at www.quickfds.com. We will request to provide your email address, so we can automatically send you a new version of the SDS when a future update would occur.

TECHNICAL SUPPORT & FREE-OF-CHARGE TESTING

Inventec has a worldwide dedicated Technical Support team to help you along the different stages of our cooperation.

Depending on your request, we provide online or onsite support

- to select the right product based on your specific needs
- to assist you in your product qualification process
- to guide you with the initial set up of you process at all your worldwide manufacturing facilities
- to provide fast response on technical issues which could occur at any time during mass production

Customers are also welcome in our CLEANING CENTERS to see the process in action and to get convinced by our solutions. We cover water- and solvent based processes.

Inventec is unique in the world by developing not only cleaning materials but also soldering and coating solutions. These materials are very closely linked with each other from a process point of view. Talking to our Technical Team, who understands very well these 3 different product groups, will help you greatly to overcome technical challenges within your overall process.

Contact our technical support via contact@inventec.dehon.com or your local sales representative.

ABOUT INVENTEC

Inventec is a global provider of SOLDERING, CLEANING & COATING materials for Electronic, Semiconductor and Industrial applications. For over 60 years we have shown leadership in innovation by putting HEALTH IMPACT, SUSTAINABILITY and RELIABILITY at the core of our product development.

With ISO 9001 & 14001 production sites in France, Switzerland, USA, Mexico, Malaysia and China we can guarantee a smooth and cost-effective supply chain.

We supply to many industries but the excellent performance of our products in applications which demand high reliability, leads us to focus especially on the AUTOMOTIVE, AEROSPACE, SEMICONDUCTOR, ENERGY and MEDICAL industry.

www.inventec.dehon.com



S O L D E R I N G • C L E A N I N G • C O A T I N G

In accordance with the Annex II of Directive 2011/65/UE (RoHS), including its amendments, we certify that this product does not contains quantities above 0.1% of Hg, Pb, Cr VI, PBB, PBDE, DEHP, BBP, DBP, DIBP and above 0.01% of Cd

This data is based on information that the manufacturer believes to be reliable and offered in good faith. In no event will INVENTEC PERFORMANCE CHEMICALS be responsible for special, incidental and consequential damages. The user is responsible to the Administrative Authorities (regulations for the protection of the Environment) for the conformity of his installation.

Inventec Performance Chemicals – 26 rue de Coulons. 94360 Bry-sur-Marne, France
Limited company with capital of 600 000€ - 964 500 706 RCS Créteil