



COOLING

# THERMASOLV™ IM1

DIELECTRIC HEAT TRANSFER FLUID  
BOILING POINT: 61°C/142°F  
MEDIUM LOW GWP

## BENEFITS

THERMASOLV IM1 is a dielectric heat transfer fluid, dedicated for 1-phase or 2-phase immersion or direct cooling systems. Its high electrical insulation properties allows to immerse electronics & electrical devices under power in the fluid. The favorable characteristics of the product's viscosity, density and surface tension allows optimal surface contact, which contributes to a superior heat transfer performance.

The very good compatibility with all metals, a wide range of plastics & elastomers and the chemical stability of the fluid, makes THERMASOLV IM1 an ideal fluid for immersion cooling.

THERMASOLV IM1 is formulated with safety in mind. It is non-toxic, has no mentioning of any EUH-phrases, is non-flammable and has no flash point. It also has fire extinguishing properties, which provides extra protection in case of fire. It is also a great sustainable solution as it has no ODP, medium low GWP and can be offered for recycling when needed.

PERFORMANCE	<ul style="list-style-type: none"> <li>Excellent thermal conductivity</li> <li>Very low surface tension</li> <li>High electrical insulation</li> <li>Low kinetic viscosity &amp; low freezing point limit the load on pumps</li> </ul>
COST	<ul style="list-style-type: none"> <li>Thermally and chemically stable in use</li> <li>Can be returned for recycling and re-use</li> </ul>
HSE	<ul style="list-style-type: none"> <li>Medium low Global Warming Potential (GWP)</li> <li>No Ozon depletion potential (ODP)</li> <li>Non-flammable &amp; no flashpoint</li> <li>Low environmental impact: GREENWAY product</li> </ul>

## SPECIFICATIONS

SPECIFICATIONS	VALUES	METHODS
Aspect	Colorless, clear	Visual
Purity (%)	> 99,5	Internal / MO.SB.10033

## CHARACTERISTICS

CHARACTERISTICS	VALUES
Flash point	No
Boiling point	61°C/142°F
Pour Point	-135°C/-211°F
Critical Temperature	195°C/383°F
Critical Pressure (MPa)	2,23
Vapor pressure (kPa @20°C)	27
Heat of vaporization (kJ/kg @BP)	112
Liquid density (Kg/m³ @20°C)	1520
Kinematic viscosity (cSt @20°C)	0,38
Specific Heat (J/kg-K @25°C)	1183
Surface tension (dynes/cm²)	13,6
Dielectric strength (kV)	28
Dielectric Constant @1kHz	7,4
Resistivity (Ohm-cm)	1,00E+09
Thermal conductivity (W/m-K)	0,069
Water content spec (ppm)	50
Solubility water in fluid (ppm weight)	95

SOLDERING  
CLEANING  
COATING  
COOLING

## PROCESS RECOMMENDATION

The best process will depend on factors such as operating conditions & equipment. Our team is ready to advise you.

THERMASOLV IM1 is a drop-in solution for other Hydrofluoroethers with a boiling point of around 61°C/142°F.

Although this product has very good compatibility properties, we cannot foresee all materials that could be exposed to the fluid. We strongly recommend testing before use.

### PROCESSES

The product can be used in the following processes:

- Immersion cooling (1-phase & 2-phase)
- Direct cooling, where the fluid flows through cold plates or tubes (1-Phase & 2 Phase)
- Specific manufacturing processes which need stable and uniform cooling
- Dielectric testing

### TEMPERATURE LIMITS

#### 1-phase system

- Recommended minimum temperature: -105°C/-157°F
- Recommended maximum temperature: 50°C/122°F

#### 2-phase system

- Boiling Point: 61°C/142°F

## PACKAGING, STORAGE & SHELF LIFE

- Store products in their original, sealed packaging in a dry place, preferably at temperatures below 30°C/86°F to prevent packaging distortion and leaks. Keep packaging away from direct sunlight.
- Shelf life is minimum 5 years from production date when kept in recommended conditions. The shelf life provides a guarantee of delivering new product and proper storage (no packaging leakages, no accidentally contamination). Once the product is used in a process it is designed for, there is no degradation of quality or performance over time.

### AVAILABLE PACKAGING



15 KG JERRYCAN




250KG DRUM

Please verify the packaging details, including volume and availability, with your sales representative, as they may vary depending on the production facility where the product is manufactured.

## HEALTH, SAFETY & ENVIRONMENT

THERMASOLV IM1 is a GREENWAY product. More info on our Greenway concept via this link.



### MAIN CONTRIBUTORS WHICH REDUCE IMPACT:

#### HUMAN HEALTH & SAFETY

- Non-flammable, no flashpoint & no EUH risk phrases: 100% safe for storage and when used in equipment
- Non-toxic, no corrosive impact & no S risk phrases

#### ENVIRONMENT PROTECTION & RESOURCES SAVINGS

- No environmental hazard: no H labelling regarding environment
- Can be returned for recycling and re-use: ECOPROGRAM
- Low viscosity: reduced energy use for pumps

PROPERTIES	IM1
Ozone Depleting Potential (ODP)	0,00
Global Warming Potential (GWP)	460
VOC	yes
Flashpoint	no

GWP calculation according to FGAS3

Contains no Reach Substances (on Candidate list, Annex XIV & XVII) / Contains no persistent organic pollutant (EC 850/2004) / Contains no Import/Export Hazardous substances (EU 649/ 2012)

Used polluted product can be returned to us for recycling if regulations permit. Please contact your local sales contact for more details on our **ECOPROGRAM**.

Please refer always to the Safety Data Sheet (SDS or MSDS) prior to use. Our SDS can be downloaded at [www.quickfds.com](http://www.quickfds.com). We will request to provide your email address, so we can automatically send you a new version of the SDS when a future update would occur.

## TECHNICAL SUPPORT & FREE-OF-CHARGE TESTING

Inventec has a worldwide dedicated Technical Support team to help you along the different stages of our cooperation.

Depending on your request, we provide online or onsite support

- to select the right product based on your specific needs
- to assist you in your product qualification process
- to guide you with the initial set up of your process at all your worldwide manufacturing facilities
- to provide fast response on technical issues which could occur at any time during mass production

Contact our technical support via [contact@inventec.dehon.com](mailto:contact@inventec.dehon.com) or your local sales representative.

## ABOUT INVENTEC

Inventec is a global provider of CLEANING, SOLDERING, COATING and COOLING materials for Electronic, Semiconductor and Industrial applications. For over 60 years we have shown leadership in innovation by putting HEALTH IMPACT, SUSTAINABILITY and RELIABILITY at the core of our product development.

With ISO 9001 & 14001 production sites in France, Switzerland, USA, Mexico, Malaysia and China we can guarantee a smooth and cost-effective supply chain.

We supply to many industries but the excellent performance of our products in applications which demand high reliability, leads us to focus especially on the AUTOMOTIVE, AEROSPACE, SEMICONDUCTOR, ENERGY and MEDICAL industry.

[www.inventec.dehon.com](http://www.inventec.dehon.com)



SOLDERING  
CLEANING  
COATING  
COOLING

In accordance with the Annex II of Directive 2011/65/UE (RoHS), including its amendments, we certify that this product does not contain quantities above 0.1% of Hg, Pb, Cr VI, PBB, PBDE, DEHP, BBP, DBP, DIBP and above 0.01% of Cd

This data is based on information that the manufacturer believes to be reliable and offered in good faith. In no event will INVENTEC PERFORMANCE CHEMICALS be responsible for special, incidental and consequential damages. The user is responsible to the Administrative Authorities (regulations for the protection of the Environment) for the conformity of his installation.

Inventec Performance Chemicals – 26 rue de Coulons. 94360 Bry-sur-Marne, France  
Limited company with capital of 600 000€ - 964 500 706 RCS Créteil